

ATA adapterji in VoIP prehodi Grandstream



Model	HT801 V2	HT802 V2	HT812 V2	HT813	HT814 V2	HT818 V2
Vrsta naprave	ATA z 1 vrati FXS	ATA z 2 vratoma FXS	ATA z 2 vratoma FXS in gigabitnim usmerjevalnikom	Hibridni ATA z vrati FXS in FXO	Prehod FXS s 4 vrati in gigabitnim usmerjevalnikom	Prehod FXS z 8 vrati in gigabitnim usmerjevalnikom
Analogna vrata	1 × FXS (RJ11)	2 × FXS (RJ11)		1 × FXS, 1 × FXO (PSTN) z rezervno linijo (lifeline)	4 × FXS (RJ11)	8 × FXS (RJ11)
Računi SIP	1 profil SIP	2 profila SIP				
Omrežni vmesnik	1 × 10/100 Mb/s		2 × 10/100/1000 Mb/s (WAN, LAN)	2 × 10/100 Mb/s (WAN, LAN)	2 × 10/100/1000 Mb/s (WAN, LAN)	
Usmerjevalnik NAT	-	-	Da			
Obremenitev zvonjenja	5 REN, do 1 km		3 REN, do 1 km		2 REN, do 1 km	
Glasovni kodeki	G.711, G.722, G.723.1, G.729A/B, G.726-32, iLBC, Opus			G.711, G.723.1, G.729A/B, G.726-32, iLBC, Opus	G.711, G.722, G.723.1, G.729A/B, G.726-32, iLBC, Opus	
Faks	T.38 (do 14,4 kb/s) in prepuščanje G.711					
Varnost	TLS, SRTP, HTTPS					
Samodejna konfiguracija	TR-069, datoteke XML					
Napajanje	Zunanji napajalnik 5 V DC/1 A		Zunanji napajalnik 12 V DC/0,5 A		Zunanji napajalnik 12 V DC/1 A	Zunanji napajalnik 12 V DC/1,5 A
Mere in teža	100 × 100 × 29,5 mm, 102 g	100 × 100 × 29,5 mm, 114 g	130 × 90 × 28,5 mm, 353 g	130,5 × 90,5 × 29 mm, 142 g	130 × 90 × 28,5 mm, 290 g	180 × 120 × 36 mm, 356 g

ATA adapterji in VoIP prehodi Grandstream



Model	HT841	HT881	GXW4216 V2	GXW4224 V2	GXW4232 V2	GXW4248 V2
Vrsta naprave	Prehod FXO s 4 linijami PSTN	Prehod FXO z 8 linijami PSTN	Prehod FXS visoke gostote, 16 vrat (1U)	Prehod FXS visoke gostote, 24 vrat (1U)	Prehod FXS visoke gostote, 32 vrat (1U)	Prehod FXS visoke gostote, 48 vrat (1U)
Analogna vrata	4 × FXO, 1 × FXS, rezervna linija (lifeline)	8 × FXO, 1 × FXS, rezervna linija (lifeline)	16 × FXS (RJ11 in konektor Telco)	24 × FXS (RJ11 in konektor Telco)	32 × FXS (RJ11 in 2 konektorja Telco)	48 × FXS (2 konektorja Telco s 50 pini)
Računi SIP	3 profili SIP		4 profili strežnika SIP, račun na vsaka vrata			
Omrežni vmesnik	2 × 10/100/1000 Mb/s, eno s PoE		1 × 10/100/1000 Mb/s			
Usmerjevalnik NAT	Da		-	-	-	-
Obremenitev zvonjenja	-	-	2 REN, do 1,8 km			
Glasovni kodeki	G.711, G.723.1, G.729A/B, G.726-32, iLBC, Opus		G.711, G.722, G.723.1, G.729A/B, G.726-32, iLBC, Opus			
Faks	T.38 (do 14,4 kb/s) in prepuščanje G.711					
Varnost	TLS, SRTP, HTTPS					
Samodejna konfiguracija	TR-069, datoteke XML		TR-069, datoteke XML, GDMS			
Napajanje	PoE 802.3af ali 12 V DC/1 A		12 V DC/5 A (100–240 V AC)			24 V DC/6,25 A (100–240 V AC)
Mere in teža	190 × 100 × 28 mm, 460 g		440 × 185 × 44 mm (1U), 2,4 kg	440 × 185 × 44 mm (1U), 2,6 kg	440 × 185 × 44 mm (1U), 2,76 kg	440 × 255 × 44 mm (1U), 3,36 kg